

LASER DIODE

Tel:86-769-81181256; 400-7777-956 Fax:808

E-mail:wuyb@dglanjji.com

LJ830LD60H5T 830nm 60mW 50°C Laser Diodes

■ Specifications

Wavelength: 830nm
 Light Output: 60mW CW
 Package Type: TO-18(Φ 5.6mm)

■ Absolute Maximum Ratings (Tc=25°C)

Parameter	Symbols	Ratings	Units
Optical Output	Po(CW)	60	mW
Reverse Voltage	Laser Vr	2	V
Operating Temperature	Top	-10 ~ +50	°C
Storage Temperature	Tstg	-40 ~ +80	°C

■ Electrical and optical Characteristics(Tc=25°C)

Parameter		Symbols	Conditions	Min	Typ	Max	Units
Threshold Current		I _{th}	-	-	25	35	mA
Operating Current		I _{op}	P _o =60mW	-	115	145	mA
Operating Voltage		V _{op}	P _o =60mW	-	1.9	2.1	Volts
Slope			-				
Efficiency		η	-	0.5	0.8	-	mW/mA
Beam Divergence (FWHM)	Parallel	θ ∥	P _o =60mW	8	12	14	deg
	Perpendicular	θ ⊥	P _o =60mW	30	35	40	deg
Parallel Deviation Angle		△ θ ∥	P _o =60mW	-3	-	3	deg
Perpendicular Deviation Angle		△ θ ⊥	P _o =60mW	-3	-	3	deg
Emission Point Accuracy		△X,△Y,△Z	P _o =60mW	-80	-	80	um
Lasing Wavelength		λ _p	P _o =60mW	820	830	840	nm

Im is sorting by custom's need

© $\theta \parallel$ and $\theta \perp$ are defined as the angle within which the intensity is 50% of the peak value.

